



Putzmeister

Your benefits

- Maximum power – meets all requirements of the current “Stage V” emission category
 - Higher output and more efficient through machine performance management in series
 - Hydraulic mixing unit with overload protection and reverse
 - New robust keypad improves usability
 - Auto-Power-Off – prevents the battery from draining overnight
 - Large diesel tank with 70 litres volume
 - User-friendly operation of feeder lever and air taps
-
- Optimised maintenance and service features
 - Robust design ensures value retention and high resale values
 - Made in Germany

Mixokret M 760 Stage V “Green Efficiency”



Semi-dry
floor screed

- **Cement screed**
- **Calcium sulphate screed (anhydrite)**
- **Magnesia screed**



Special
applications

- Sand
- Aggregate

The M 760 Stage V – Green Efficiency conveys screed up to 190 metres** horizontally and 135 metres** vertically.

The keypad with innovative, colour LED display in the control cabinet makes operation incredibly simple and efficient. The menus for troubleshooting and servicing improve efficiency.

Maximum power and efficiency is available with the Deutz diesel engine (emission category Stage V). The integrated diesel particle filter cleans the exhaust gases and protects our environment from pollution.

For further information related to technical details or application, please contact your local Putzmeister dealer.



Maximum drive power thanks to the 44.5 kW Deutz engine – this meets all requirements of the current „Stage V“ emission category.



User-friendly robust keypad clearly arranged and easy to use – thanks to the „follow the blue light“ principle



Machine performance management in series allows adjustment of engine power as needed. This can save fuel or provide extra power.

Technical data

M 760	DH	DHB	DHBS
Mixer drum	260 l, 200 l useful capacity		
Delivery rate*	4 m ³ /h	4.8 m ³ /h	5 m ³ /h
Delivery pressure	8 bar	8 bar	8 bar
Delivery range**	190 m horizontally / 135 m vertically (45 storeys)		
Compressor	4.8 m ³ /min; cut-off pressure 8 bar		
Engine	Diesel, 3-cylinder Deutz with turbocharging, 44.5 kW (emission category Stage V)		
Weight	1,715 kg	1,840 kg	1,900 kg
Tank capacity	70 l	70 l	70 l
Length	4,780 mm	5,075 mm	5,075 mm
Width	1,480 mm	1,480 mm	1,480 mm
Height	1,520 mm	2,431 mm	2,431 mm
Filling height	820 mm	400 mm	400 mm
Maximum grain size	16 mm	16 mm	16 mm
Chassis	braked, approved for speeds up to 80 km/h		
Mixing unit	hydraulic with overload protection and reverse		
Special feature	Basis version	with hydraulic feeder	with hydraulic feeder and scraper

* The delivery rate is theoretical and depends on the pump pressure.

** The data is based on experience and depends on the material properties.

□ Optional ■ Standard

Equipment

Auto-Power-Off	■
Car coupling	■
Central lubrication system	■
Discharge stand	■
Fuel gauge in display	■
Grease pump for lubrication system	■
Instruction manual and spare parts list	■
Lever Press with hose	■
Lifting eye	■
Performance management	■
Working lights	■
Blockage alert	□
Conversion to 100 km/h	□
High-pressure cleaner	□
Light holder 24 V	□
Location system	□
Mixing meter	□
Mixing time adjustment	□
Protection plate for feeder	□
Special canopy paint in RAL colours/Custom labelling	□
Support feet	□
Toolbox	□
Truck coupling	□
Water dosage (integrated)	□
Wear plates at front end	□
Wear plates at the dome	□
Wear plates (Hardox 6 mm)	□
Wear plates (Hardox 8 mm)	□

Putzmeister Mörtelmaschinen GmbH

Max-Eyth-Straße 10 · 72631 Aichtal / Germany
P.O.Box 2152 · 72629 Aichtal / Germany
Tel. +49 7127 599-0 · Fax +49 7127 599-743
mm@putzmeister.com · www.putzmeister.com

